

SCHEDULE P65[©]

Pre 65 North Island Race Series TECHNICAL REGULATIONS 2025 - 2026

PREAMBLE

Basic premise:

- All cars to remain standard.
- The practice of removing or leaving body panels off is not permitted.
- The only modifications permitted are those contained in these regulations.
- Any effort to accommodate any secondary modification, to permit those modifications allowed to function, is not permitted.

Spirit of the Regulations: It should also be noted that these specifications would be interpreted on the basis that if a modification is not specifically permitted; then it is not allowed. Efforts to bend, find or take advantage of loopholes in the rules will be deemed not to be in the spirit of the regulations.

COMPETITOR RECORD OF AMENDMENTS ISSUED TO THIS SCHEDULE

Use this table to keep a record of all official 'Manual / Championship Amendments' issued during the season relative to this Schedule;

Amendment Number	Issue/Effective date	Regulation reference	Subject / Notes

1.0 GENERAL INFORMATION RELATIVE TO THIS SCHEDULE

- 1.1** All text changes from the previous issue of this Schedule are highlighted such. Text changes for grammatical and/or formatting reasons are not highlighted.
- 1.2** All cars competing in Events to which these regulations apply shall have a valid MotorSport NZ logbook.
- 1.3** **TECHNICAL ELIGIBILITY AND SAFETY EQUIPMENT ENQUIRY:** Where any doubt may exist in understanding any regulation contained within this Schedule it will be understood that it is the Competitors obligation to enquire as to the correct interpretation. All technical eligibility and/or safety equipment enquiry shall be submitted in writing to:
- (1) The Series Scrutineer, as detailed in the Series Articles, or in their absence to
 - (2) The MotorSport NZ Technical Manager
- All enquiries should detail the article in question and the specific subject matter.
 - A written reply will always be given to a written enquiry.
 - On matters of technical eligibility and/or safety compliance, a verbal statement will have no validity.

2.0 DEFINITIONS

- 2.1** Definition of terms used within this Schedule shall be referenced from the National Sporting Code, Appendix Two Schedule A, and as detailed below:
- **“Saloon”** means a two(2) or four(4) door vehicle including the hatchback, fast back and station- wagon variants of the same with a fixed roof with factory seating for four(4) occupants.
 - **“GT”** means a performance derived two (2) door closed vehicle with a 2 + 2 configuration.
 - **“Engine”** means the cylinder block, the cylinder head(s), the crankshaft and the camshaft, which must be based on a pre-1965 Series Production saloon car engine.
 - **“Original”** means the factory fitted part for that make, model and year.
 - **“Replica”** means a “reasonable” copy of the original part in design and style of the original part.
 - **“Front Valance”** means a bolt/screw on panel behind the bumper, generally attached beneath the grill and as a finishing panel under the front guards.
 - **“Nose Cone”** means a complete bolt/screw on front panel, i.e. Mustang; the panel generally contains the grill and head lights etc. and is bolted to the front guards

3.0 ELIGIBLE VEHICLES

- 3.1** For Series Production Vehicles that were in mass production (and available on general - */catalogue sale) prior to the 31st December 1965, of which a minimum of 1000 units were produced.
- 3.2** The Engine castings shall have been in Series Production prior to 31st December 1965, or a post 1965 cylinder block and/or crankshaft from the same generic engine family as the pre 1965 cylinder block and/or crankshaft (retaining the same cylinder configuration and the same number of cylinders) produced by the same manufacturer as the car, from the same country of origin as the car and fitted within the confines of the original engine compartment.

Note: *All post 1965 cylinder blocks and/or crankshafts are to be as per list, refer Article 8.12.*

- 3.2.1** A Post-1965 engine block from the same vehicle manufacturer may be used in compliance with Article 8.12 below. These engines shall have seals applied in accordance with Article 4.1.
- 3.2.2** Vehicles with existing 0.060inch/1.5mm over-bore (or greater) engines shall be permitted to compete until the engine block is replaced.

3.2.3 Sleeving of Cylinder Blocks

Cylinder blocks may be sleeved to recover or salvage a cylinder block, all bores, if required to return the block to the original pre-sleeved capacity.

It is not permitted is to sleeve a cylinder block to gain engine capacity.

- 3.3** Any cylinder head (as fitted to the subject Series Production Vehicle) that was in series production prior to 31 December 1965 or a direct replacement cylinder head must be of the same dimensions as the original series production cylinder head.
- 3.3.1** Details of the replacement cylinder head shall be submitted to the Series Scrutineer prior to order. The data sheet for the cylinder head shall be delivered to the Series Scrutineer on delivery of the cylinder head who will review the specifications and approve the application if acceptable.
- 3.3.2** Alloy cylinder heads are permitted subject to Series Scrutineer and Committee approval. Approved cylinder heads must not be modified from the production specifications.

4.0 GENERAL CONDITIONS

- 4.1** Official Series Seals may be applied by the Series Scrutineer to components and/or assemblies of components in compliance with Appendix Two, Schedule A, Article 3.7. All seals shall be clearly detailed in the vehicles MotorSport NZ logbook.

Note: *These seals may not be removed except where express written permission by the Series Scrutineer is obtained.*

- 4.2** The Competitor or the Series Scrutineer may request that an engine be sealed at the time of assembly (meaning it is able to be checked prior to assembly) or 'retro' sealed (sealed after assembly, meaning it is unable to be checked). Any engine sealed in such a fashion may not be stripped, nor the seal removed unless in the presence of the Series Scrutineer, or their appointed assistant/s.
- 4.3** Any infringement of the seal management program or any technical breach of the technical regulations may result in a penalty being applied.

- 4.4 The engine, gearbox and rear axle/final drive (differential) shall remain in the confines of their original compartments within the bodyshell.
- 4.5 Cars must be presentable in workmanship and appearance.

5.0 SAFETY EQUIPMENT REQUIREMENTS

- 5.1 The following **safety equipment** shall be fitted to the competing car:
 - 5.1.1 A safety cage shall be installed, in full compliance with Schedule A requirements.
 - 5.1.2 A minimum 5-strap safety harness shall be installed in full compliance with Schedule A.
 - 5.1.3 A Competition Seat in full compliance with Schedule A shall be fitted.
 - 5.1.4 A fire extinguisher in full compliance with Schedule A shall be fitted.
 - 5.1.5 A high 'rain' light shall be mounted inside the rear window on the centreline facing rearward in a position that does not restrict rearward vision. The light may double as a 'stop light' and must be a red lens LED type light. The light is in addition to the original series production taillights or replicas as laid out in Article 6.2 that are in good working order.
- 5.2 Double intrusion bars shall be fitted adjacent to the driver's side of the vehicle and, if applicable, to the passenger's side of the vehicle.
- 5.3 The following safety equipment **may** be fitted to the competing car:
 - 5.3.1 Alternative braces that form an integral part of the safety cage may only replace factory tower braces.

6.0 BODYSHELL, VEHICLE EXTERIOR and SUB-FRAMES

- 6.1 Lightening of the bodyshell will be confined to the bonnet, boot lid, doors and associated hinges, brackets and supports, excepting all outer door handles. Alternative materials being alloy or fibreglass may be used. The external appearance is to remain the same as original. Unused brackets and mounts may be removed.
 - 6.1.1 Vehicles must be fitted with their original bumper irons
 - 6.1.2 Where a headlight is removed. A replica in general style and look must replace it. It is not permitted to remove the headlight, backing and bowl and leave the aperture open. If the headlight aperture is used for brake cooling it must be a closed scoop of minimal opening. The external look must still replicate the original light.
- 6.2 Additionally, replica parts of alternative material may replace the headlights, park lights, taillights and surrounds, grilles and surrounds, bumpers, front valances, nose cones and door glass frames. Refer Article 2.1.
- 6.3 Fibreglass replica panels may replace original bolt-on type front mudguards providing the replica panel is identical in appearance and weight to the original panel. Welded on front guards may be replaced with fibreglass guards, but they must be glued and bolted to be in line with the other model's replacement front guards. If front guards are welded from factory, they must be glued and bolted on. If front guards are only bolted on from factory they may be only bolted on.

Note: All mudguards and moulds to be inspected and approved by the Committee.

- 6.4 All windows may be replaced in compliance with Schedule A.
- 6.5 Wheel arch flares are authorised provided they cover at least 1/3 of the tyre circumference and do not exceed the production bodysell width by more than 100mm, with the material being free.
- 6.6 The original outer mudguards must remain in their original position but can be relieved or flared (no more than 100 mm) for tyre clearance.
- 6.7 Wheel tubs may be modified from the centre-line of the tub to the outer guard, but tubs to remain sealed.
- 6.8 Rear doors may be permanently fixed but must retain their original external appearance.

7.0 VEHICLE INTERIOR

- 7.1 Interior trim may be removed provided a tidy appearance is maintained. Fire retardant materials are recommended. The complete dash panel may be removed in which case an alternative panel of similar dimensions to the original dashboard shall be fitted.
- 7.2 All seating shall be removed. The Competition Seat shall be mounted (to the left or to the right of the vehicle centre-line) no further rearward than the original seat.

A front passenger seat may be fitted (to the right or left of the vehicle centre-line) no further rearward than the original seat; each must be in compliance with Articles 5.1.2, 5.1.3 and 5.2.
- 7.3 Instrument mounting panels may be fabricated.
- 7.4 The floorpan may be modified for the installation of rear suspension tramp rods. The floor and/or sill panels may be modified for exhaust installation.
- 7.5 The transmission tunnel immediately above the bellhousing / gearbox may be modified for clearance purposes provided the tunnel remains an integral part (welded) of the bodysell.
- 7.6 The front bulkhead may be modified solely for ignition distributor and/or carburettor clearance.
- 7.7 All minor components (not the engine, gearbox and rear axle/final drive) may be relocated.
- 7.8 The fuel tank is free provided Schedule A compliance is maintained. All bodysell openings created by these changes shall be covered with a steel/alloy panel.
- 7.9 Brake clutch and accelerator pedals and mounting systems are free.

8.0 ENGINE SPECIFICATIONS

- 8.1 The engine bore size and compression ratio, are free.
- 8.2 The cylinder block may be modified for steel main bearing caps (2 or 4 bolt).
- 8.3 The crankshaft bearing journals may be machined / cross-drilled but the stroke shall remain standard. The crankshaft may be surface treated / balanced but the casting numbers must remain clearly visible.

8.4 Approved rev limiters to be fitted to engines with non-standard crankshafts, rev limits to be set by the committee.

8.4.1 Rev limits as set by Committee (2004)

- Class "A" V8 7500rpm
- Class "B" 6 Cylinder 7500rpm
- Class "C" Open 4 Cylinders 8000rpm
- Class "D" Under 1400cc 8000rpm
- Class E 2001 to 2850cc 7500rpm
- One exemption is the MK3 Zephyr in allowing the Falcon 200 ci 7 bearing engines, both the Technical and full Committee restricted the RPM to 7000 max.

8.5 Lubrication systems are free.

8.6 Heads may be ported and polished. Port and combustion chamber design is free.

8.7 Identification marks / numbers on cylinder heads, blocks, and crankshafts must not be altered.

8.8 Water and oil cooling systems may be modified with a minimum of bodysell modification (excepting the water radiator, which shall remain in its original position). Alternative homologated radiator position is allowed.

8.9 Sump protection guards may be fitted.

8.10 All other engine parts are free.

8.12 POST 1965 ENGINE LIST

8.12 The following engine blocks and/or crankshafts have been approved for use in this Series:

- Ford 302 Windsor cylinder block only, (excludes the BOSS, SVO & MEXICO blocks)
- Chrysler LA 318 (cylinder block only)
- Rootes 930 Sunbeam Imp cylinder block & crankshaft
- Ford pre-crossflow 1300 5 bearing standard production cylinder block and crankshaft.
- Ford pre-crossflow 1500 standard production cylinder block.
- Ford crossflow 1600 cylinder block only.
- Ford 1600cc cross flow cylinder head
- Ford 1600cc crankshaft.
- Ford 7 main bearing 200ci low deck block and crankshaft restricted to 7000rpm with an approved rev limiter.
- BMC/BLMC 1300cc A Series block and crankshaft.
- Triumph 2500cc block and crankshaft.
- D Class cars are permitted engines as manufactured prior to 31 December 1967. (Refer also to Article 2.1 and Article 3.1 above).

- Ford 302 crankshaft

8.12.1 In addition to the engines authorised in Article 8.12 above, a Post-1965 engine block from the same vehicle manufacturer, or an after-market block, of the same capacity and constructed from the same material may be used provided the original 1965 stroke is retained. A maximum over-bore of 0.060inch from the original standard 1965 bore is permitted.

8.12.2 Lotus twin cam engines can only be fitted to a genuine 2-door Cortina bodyshell

9.0 INDUCTION / EXHAUST SYSTEM

9.1 Carburettors and fuel delivery systems are free, provided no forced induction (by mechanical means) and/or injection systems are used.

9.2 The exhaust system is free, provided Schedule A compliance is maintained.

10.0 FUEL SYSTEM

10.1 The fuel system is free, provided Schedule A compliance is maintained.

10.2 Fuel: The only fuels authorised for use in competing vehicles at any Round of this Series is as detailed in Appendix Two, Schedule A, Article 3.9 Fuel, excepting all Pre65 vehicles that have been issued with a MotorSport NZ exemption may use leaded avgas / racegas, until such time as an alternative unleaded fuel which meets the requirements of the class.

11.0 TRANSMISSION

11.1 The gearbox casing and tail-shaft housing must have been in series production prior to 31/12/65, although the internal components are free. Any post 1965 Gearboxes and tail-shafts with 'H' pattern shift utilizing four forward gears are permitted.

11.2 The axle/differential must be the same type and material as fitted standard to the car, the internal components are free, excepting as detailed in Article 11.3 below.

11.2.1 Where differential housing have been changed the total width of the differential housing, with wheels attached, will remain within the confines of the bodywork

11.3 Locked, limited-slip and/or traction control devices are not authorised in the differential or any part of the vehicle. Including mechanical, electronic and launch control devices. Oversize or extra shims or thrust washers fitted for the sole purpose of reducing the free movement of the differential or spider gears is prohibited. The unloaded wheel must spin freely at all times.

11.4 A steel driveshaft safety hoop must be fitted under the front section of the driveshaft of rear wheel drive cars.

11.5 The clutch and bell housing are free.

11.6 Manual sequential gearboxes, sequential gear kits or sequential gear shifting mechanisms are not permitted.

11.7 The gearbox cross member may be strengthened, altered or replaced.

11.8 Triumph Vitesse Rear Axle: Due to safety concerns, the fitting of a Datsun 180B type axle is permitted. An additional lower support arm is permitted to assist with the mounting of the unit.

12.0 IGNITION and ELECTRICAL SYSTEMS

- 12.1 Ignition:** The type of ignition system is free.
- 12.2** An operational electric starter motor must be fitted, capable of starting the engine.
- 12.3** Charging systems are optional.
- 12.4** The battery shall comply with the fixation requirements of Schedule A and may be relocated.

13.0 SUSPENSION

- 13.1** The front and rear suspension must be of the same design as per the original vehicle.
- 13.2** Each suspension mounting point may be strengthened and/or moved a maximum of 50mm (the mounting point being the attachment bolt) from its original position in relation to the chassis, excepting the shock absorber mounts.
- 13.3** Additional suspension components such as turret braces, anti-roll bars, panhard rods, watts linkage and tramp bars may be fitted provided that they are really additional, meaning the vehicle will drive / operate safely when the additional component is removed.
 - 13.3.1** Chassis members are the box sections that run fore and aft of the vehicle. These sections cannot be cut or altered.
 - 13.3.2** Strengthening panels that run between the parallel chassis rails, and are not box sections, are considered to be supporting panels. They may be modified but not removed.
- 13.4** Anti tramp devices may be fitted with a maximum of two forward links and one lateral link only. (An 'A' frame is considered one link provided it is a one-piece rigid assembly. Watts linkages are considered one link). Only these additional linkages as described may be mounted with bushes or self-aligning bearings.
- 13.5** The vehicles ride height, spring rate, shock absorbers and their mountings and mounting points are free, excepting that no self-aligning and/or spherical joints/bearings are permitted. Fabricated shock absorber towers are authorised provided they do not require any modification of the chassis.
- 13.6** Suspension mountings and the method of attachment is to be as per the original vehicle, namely by bushes, ball-joints, U-bolts, shackles etc. Bushes may be of alternative material. Spherical bearings may be used on the top mount of the front struts and front sway bar only.
- 13.7** Bolt on front axle beam/front suspension cross member may be strengthened, altered or replaced.

14.0 BRAKING SYSTEM

- 14.1 Front and rear brakes:** Drums can be replaced with larger drums, discs with larger discs.
- 14.2** Wheel cylinder and bore size is free.
- 14.3** Front brakes are free respecting a maximum of four(4) pistons per calliper and a maximum size of 310mm for disc diameter. Rear Brakes are free respecting a maximum of two(2) pistons and a maximum size of 310mm for disc diameter. Vented and cross drilled OEM and

replacement disc rotors are permitted provided they are commercially available for sale from a reputable parts retailer and can be fitted without any modifications. This interpretation does not include, hi tech aftermarket Racing specific, exotic carbon metallic or similar type, disc rotors.

- 14.4 Brake backing plates may be modified or removed.
- 14.5 No drilling of the disc or drum friction surface is authorised.
- 14.6 Brake master cylinder and activating method is free.
- 14.7 If a single master cylinder is fitted, the vehicle must have a mechanical handbrake.
- 14.8 All friction materials (linings) are free.
- 14.9 Any air ducting for brake cooling must be confined within the original bodywork, using existing bodysHELL apertures. Panels behind existing apertures may only be relieved by the minimum amount to allow ducting to pass through.
- 14.10 No mechanical or electronic anti-lock-up braking devices (ABS) are permitted.

15.0 STEERING

- 15.1 The steering system must be of the same design as per the original vehicle.
- 15.2 The steering box / steering rack internal components are free. Additionally, the steering wheel is free. All steering components must be in accordance with Schedule A.
- 15.3 Spherical ball rod ends may be used on the steering intermediate steering rod only in compliance with Schedule A and Pre65 technical requirements, type and size.

16.0 ROAD WHEELS and TYRES

- 16.1 Commercially available wheels of steel or alloy shall be used. A maximum rim width of 20.32cm (8 in.) applies.
- 16.2 The wheel rim diameter is:
 - Class "A" cars up to 17"
 - Class "B" cars up to 15"
 - Class "C" cars up to 14"
 - Class "D" cars up to 13"
 - Class "E" cars up to 15"

Where a car has wheels larger than the class standard wheel, size may only be increased by 1" (25mm) to a maximum of 17".

- 16.3 The control tyre is open, as approved by the Committee. Tyres must be DOT Rated.
- 16.4 **Wet Races:** When an announcement as detailed in Appendix Four, Schedule Z, Article 13.9 of the current New Zealand MotorSport Manual is made by the Event Director or Clerk of the Course (declared 'wet'), a DOT Rated treaded tyre must be used. Racing "wet" tyres are not permitted.

- 16.5** The tyre tread must remain within a vertical line from the top outer edge of the guard or flare to the centreline of the axle.

17.0 GENERAL

- 17.1** Nuts, bolts, circlips, pins, springs, clips, paintwork, coolants and lubricants are free.

18.0 TIMING TRANSPONDERS

- 18.1** Such electronic timing systems shall be mounted securely to the vehicle forward of the centre line of the front wheels, and within 200mm-500mm from the front edge of the front bumper. It must be mounted within 500mm off the ground and may be mounted on either side of the vehicle.